Workshop on Advanced Data Collection with Multi-Axis Goniometry MADaC 2015

Synchrotron SOLEIL - L'orme des Merisiers Saint-Aubin, France 12th-14th of November 2015

ABSTRACTS BOOKLET

Summary

- Welcome
- Organizing Committee
- General Program
- Abstracts
 - Thursday, November 12th Sessions I & II
 - ✓ Friday, November 13th Sessions III & IV
- Practical Applications

Workshop on Advanced Data Collection with Multi-Axis Goniometry

MADaC 2015

Synchrotron SOLEIL - L'orme des Merisiers

Saint-Aubin, France

12th-14th of November 2015

Welcome

Multi-axis goniometry, more simplistically known as kappa goniometry, is being installed at a growing number of macromolecular crystallography end-stations worldwide. However, the great potential of the technique when approaching challenging structure determination remains to be fully exploited. This workshop, second of its kind, brings together experimenters and developers experts in the field in order to identify current bottlenecks and to explore possible solutions using aspects of kappa goniometry optimised for data collection strategies and processing for facilitating phase retrieval of difficult samples.

In image to the first workshop, both lectures and practicals will be given. Data collection practicals will be performed at beam line PROXIMA-1 of the Synchrotron SOLEIL.

Bienvenue

La goniométrie à axes multiples, mieux connue sous le nom de goniométrie kappa, est mondialement utilisée sur un nombre croissant de lignes de lumière dédiées à la cristallographie des macromolécules. L'énorme potentiel de cette technique dans le cadre de déterminations problématiques de structures cristallines reste à exploiter dans sa profondeur. Pour sa deuxième édition, ce workshop réunit des expertises dans ce domaine afin de tenter d'identifier les problèmes bloquants et trouver des solutions qui feront appel à la goniométrie kappa optimisée pour l'établissement de stratégies de collectes de données et pour faciliter le phasage d'échantillons problématiques.

A l'instar du premier workshop, il sera composé aussi bien de conférences invitées que de travaux pratiques.

Les TP sur l'acquisition de données auront lieu sur la ligne PROXIMA-1, du Synchrotron SOLEIL.

Workshop on Advanced Data Collection with Multi-Axis Goniometry MADaC 2015

Synchrotron SOLEIL - L'orme des Merisiers Saint-Aubin, France 12th-14th of November 2015

ORGANIZING COMMITTEE

Leo CHAVAS

Camille DUCROT

Frederique FRAISSARD

Tatiana ISABET

Pierre LEGRAND

Jean-Marc LUCACCHIONI

France POCHARD

Martin SAVKO

William SHEPARD

Serena SIRIGU

Workshop on Advanced Data Collection with Multi-Axis Goniometry MADaC 2015

Synchrotron SOLEIL - L'orme des Merisiers Saint-Aubin, France 12th-14th of November 2015

Programme

Thursday, November 12th

- 13:00 13:50 Registration & Welcome coffee
- 13:50 14:00 Welcome word, Jean Daillant, Director, Synchrotron SOLEIL

SESSION I

Multi-axis goniometry and strategies

Chairperson: Leonard CHAVAS

- 14:00 14:40 Optimising and driving Synchrotron experiments as a third party **Gérard Bricogne** *Global Phasing Ltd., Cambridge, UK*
- 14:40 15:20 A Better data collection strategy: You can always use a lower dose **Meitian Wang** - Swiss Light Source, Paul Scherrer Institute, Villigen, Switzerland
- 15:20 16:00 Weak anomalous signal scaling: On extracting the needle from the haystack **Nicolas Foos** *Synchrotron SOLEIL, Gif-sur-Yvette, France*
- 16:00 16:30 Coffee break

SESSION II

Kappa-goniometry at synchrotrons and further developments

Chairperson: Martin SAVKO

- 16:30 17:00 Native SAD: The magic bullet for experimental phasing? Vincent Olieric - Swiss Light Source, Paul Scherrer Institute, Villigen, Switzerland
- 17:00 17:30 (Mini-)Kappa Diffractometers on EMBL@PETRAIII Beamlines Gleb Bourenkov – EMBL, Hamburg, Germany
- 17:30 18:00 Multi-axis goniometry for MX at Diamond Light Source **Ralph Flaig** *Diamond Light Source, Didcot, UK*
- 19:00 20:30 Dinner

Friday, November 13th

SESSION III

Data processing for advanced data collection protocols

Chairperson: Pierre LEGRAND

- 09:00 09:30 Inside the black box of data processing Harry Powell - MRC Laboratory of Molecular Biology, Cambridge, UK
- 09:30 10:00 Processing multi-axis, multi-wavelength and interleaved datasets with autoPROC Clemens Vonrhein - Global Phasing Ltd., Cambridge, UK
- 10:00 10:30 Diffraction experiments of arbitrary geometry **Tim Grüne -** Swiss Light Source, Paul Scherrer Institute, Villigen, Switzerland
- 10:30 11:00 coffee break

SESSION IV

Case studies

Chairperson: Serena SIRIGU

- 11:00 11:30 The use of a mini-kappa goniometer head for diffraction experiments at the ESRF Andrew McCarthy ESRF, Grenoble, France
- 11:30 12:00 The use of multi-axis goniometers for phasing of glycoprotein crystals **Thomas Krey** - *Institut Pasteur and CNRS UMR 3569,Paris, France*
- 12:00 12:30 Experimental design in MX: A skill not to be ignored Andrew Thompson - Synchrotron SOLEIL, Gif-sur-Yvette, France
- 12:30 14:00 Lunch
- 14:00 18:00 Practical applications
- 19:00 20:30 Dinner

Saturday, November 14th

- 09:00 12:30 Practical applications
- 12:30 14:00 Lunch
- 14:00 Departure

ABSTRACTS

Thursday, November 12th, 2015

SESSION I & II

MADaC - 2015

Thursday, November 12th

SESSION I Multi-axis goniometry and strategies

Chairperson: Leonard CHAVAS

IT-01	Optimising and driving Synchrotron experiments as a third party <i>G. Bricogne</i>
IT-02	A Better data collection strategy: You can always use a lower dose <i>M. Wang</i>
IT-03	Weak anomalous signal scaling: On extracting the needle from the haystack <i>N. Foos</i>
	SESSION II Kappa-goniometry at synchrotrons and further developments Chairperson: Martin SAVKO

IT-04	Native SAD: The magic bullet for experimental phasing? V. Olieric
IT-05	(Mini-)kappa diffractometers on EMBL@PETRAIII beamlines <i>G. Bourenkov</i>
IT-06	Multi-axis goniometry for MX at Diamond Light Source <i>R. Flaig</i>

Optimising and Driving Synchrotron Experiments as a Third Party

<u>G. Bricogne</u>, C. Flensburg, P. Keller, W. Paciorek, & C. Vonrhein

Global Phasing Ltd., Sheraton House, Castle Park, Cambridge CB3 0AX, UK

ABSTRACT

The ever-increasing speed of MX beamline instrumentation is leading to ever-stronger emphasis being placed on brevity of execution as the main design goal for data collection protocols, often to the exclusion of other criteria that would aim at achieving higher data quality. This can be counter-productive, especially, but not only, for phasing experiments.

Global Phasing, among others, has been interested in bucking that trend by creating combined capabilities for the fast design of optimal strategies and the direct supervision of their execution on an actual beamline. Our approach has been to aim for a full "third-party design and control" capability rather than for separate add-on programs that would need to be invoked by local software on each specific group of beamlines running under a given BCS (for Beamline Control Software).

To make such an integrated capability as transferable as possible across the huge diversity of beamline instruments and BCSs, finding the correct level of abstraction for all the components and processes involved is of paramount importance. Abstracting the processes requires focusing on the stage where description and action must dovetail.

For a strategy to achieve optimality, it needs to rely on complex sequences of measurements dictated by scientific criteria and imperatives; while in order to achieve "executability" it must be translatable into a sequence of instrumental actions available from the BCS. A common vocabulary is therefore required for the instructions in terms of which any complex strategy can be expressed, and on the basis of which the combined instrumental actions needed to execute these instructions can be requested from the BCS. We have defined such a common vocabulary and captured it into a data model for an Abstract Beamline Interface.

Progress made as part of a close collaboration with the Diamond Light Source (COL0044, on the I23 long-wavelength beamline) in implementing this paradigm into a highly adaptable workflow invoking new applications for optimal strategy design (especially, using multi-axis goniometers) will be presented, along with plans and existing collaborative links for disseminating this work to all European and several US synchrotrons.

It is expected that the uptake of this work on beamlines used in collecting diffraction data for structure-based drug discovery will enable the implementation of "Club Class" data collection on samples from which the highest-quality results are to be derived, along with the "Economy Class" data collection on samples from which only a binary answer (binds/doesn't bind) is needed.

A Better Data Collection Strategy: You Can Always Use a Lower Dose

M. Wang

Swiss Light Source, Paul Scherrer Institute, Villigen, CH-5232, Switzerland

ABSTRACT

Typical data collection in macromolecular crystallography usually consists in measuring unique reflections with minimum multiplicity and maximum X-ray dose (10 - 20 MGy). This strategy, when employed for experimental phasing, is often suboptimal. Recent advances in beamline instrumentation (namely pixel array detectors and multi-axis goniometers) have enabled new data collection protocols, which distribute the total X-ray dose in multiple data sets and multiple crystal orientations. This method can reduce systematic measurement errors effectively and improve the quality achievable for the final data. I will describe such strategies and their applications for experimental phasing.

Weak Anomalous Signal Scaling : On Extracting the Needle from the Haystack

N. Foos₍₁₎, A.Thompson₍₁₎, P. Legrand₍₁₎

(1) Synchroton SOLEIL l'orme des merisiers Saint-Aubin BP48 91192 Gif-sur-Yvette

ABSTRACT

DECIPHERING AND OPTIMISING THE SCALING STEP IN DATA-REDUCTION

Currently 80 % of the structures in the wwwPDB are determined using synchrotron radiation sources, often on beamline with tuneable wavelength and advanced experimental setup. Even if the Molecular Replacement is still the most frequent method used to solve the phase problem, experimental phasing becomes more and more accessible. The simplest phasing experiment, applicable in most cases, would be single wavelength anomalous diffraction (SAD) with the native sulfur (S-SAD). Despite this good news, in practice S-SAD is still quite challenging and only few attempts are successful.

Due to the small contribution of anomalous scatterers over the total scatterers, which leads to a relatively low $\Delta F / F$ ratio (where ΔF is the difference in intensity between Bijvoet pairs), the challenge for this method is the proper determination of the very weak anomalous signal (except for DLS-I23 beamline, which can go to very long wavelengths and hence increase the ΔF signal).

The work presented here is focused on trying to improve scaling steps during the data reduction process for this specific case. Based on already solved S-SAD structures, we attempted to determine the criteria which give the best chance of phasing success. For that purpose, we developed tools to automatically test and validate or reject different scaling settings using the XDS program₍₃₎. We observed that the best results for the phase determination was not always well correlated with the metrics currently useded to assess the guality and strength of the anomalous signal.

This observation led us to propose that, in the case of low anomalous signal, it is necessary to decrease the number of scaling parameters. For example, we show that it is best to ignore Bijvoet differences in the scaling procedure (FRIEDEL'S LAW=TRUE). This scaling schema leads to a decrease in the statistics indicators of quality but allow the calculation of better electron density maps.

^{1.} Weinert, T. et al. Fast native-SAD phasing for routine macromolecular structure determination. Nat Meth 12, 131–133 (2015).)

Rose, J. P., Wang, B.-C. & Weiss, M. S. Native SAD is maturing. IUCrJ 2, 431–440 (2015).
 Kabsch, W. XDS. Acta Crystallogr D Biol Crystallogr 66, 125–132 (2010).

^{4.} Kabsch, W. Integration, scaling, space-group assignment and post-refinement. Acta Crystallogr D Biol Crystallogr 66, 133–144 (2010)

^{5.} Dauter, Z. & Adamiak, D. A. Anomalous signal of phosphorus used for phasing DNA oligomer: importance of data redundancy. Acta Crystallogr D Biol Crystallogr 57, 990-995 (2001).

^{6.} McCoy, A. J. & Read, R. J. Experimental phasing: best practice and pitfalls. Acta Crystallogr D Biol Crystallogr 66, 458–469 (2010). 7. Klinke, S. et al. S-SAD phasing of monoclinic histidine kinase from Brucella abortus combining data from multiple crystals and

orientations: an example of data-collection strategy and a posteriori analysis of different data combinations. Acta Crystallographica Section D Biological Crystallography 71, (2015).

^{8.}Waltersperger, S. et al. PRIGo: a new multi-axis goniometer for macromolecular crystallography. Journal of Synchrotron Radiation 22, (2015).

^{9.} Schiltz, M. & Bricogne, G. Exploiting the anisotropy of anomalous scattering boosts the phasing power of SAD and MAD experiments. Acta Crystallogr D Biol Crystallogr D64, 711-729 (2008).

^{10.}Liu, Q. et al. Structures from Anomalous Diffraction of Native Biological Macromolecules. Science 336, 1033–1037 (2012).

Native SAD: The Magic Bullet for Experimental Phasing?

V. Olieric

Swiss Light Source at Paul Scherrer Institute, Villigen PSI, Switzerland

ABSTRACT

Native SAD uses the weak anomalous scattering of light elements naturally present in the target macromolecule (P, S, Cl, K and Ca). Its success relies on very accurate measurement of the reflection intensities, which is limited by both random and systematic errors, as well as radiation damage, and crystal quality. A data collection strategy [1], which can yield high quality anomalous data, was developed at beamline X06DA-PXIII at the Swiss Light Source. It consists in collecting multiple low-dose data sets on only one crystal entity in multiple orientations. The method benefits from very stable X-ray source and optics, a high-precision multi-axis PRIGo goniometer [2] and a readout noise-free PILATUS detector calibrated for low energies.

I will describe the key features of our anomalous data collection strategy and its application for native SAD phasing. I will present real-life examples, including challenging cases where our low-dose multi-orientation strategy was combined with the multi-crystal merging approach [3]. Finally, I will present first results on a fully automated and fast native SAD data collection protocol using both SmarGon (SmarAct GmbH), the commercial multi-axis goniometer based on PRIGo, and the new hybrid photon counting detector EIGER 16M (Dectris, Ltd.).

- S. Waltersperger, V. Olieric, C. Pradervand, et al. PRIGo: a new multi-axis goniometer for macromolecular crystallography. JSR, 2015, 22(4):895-900.
- 3. Q. Liu, T. Dahmane, Z. Zhang, et al. Structures from anomalous diffraction of native biolocal macromolecules Science, 2012, 1033-7.

^{1.} T. Weinert, V. Olieric, S. Waltersperger, et al. Fast native SAD phasing for routine macromolecular structure determination. Nature Methods, 2015, 12(2):131-3.

(Mini-)Kappa Diffractometers on EMBL@PETRAIII Beamlines

G. Bourenkov and T. Schneider

EMBL Hamburg Outstation, c/o DESY, Notkestrasse 85b 22607 Hamburg Germany

ABSTRACT

Macromolecular crystallography beamlines P13 and P14 are part of the Integrated Facility for Structural Biology operated by EMBL-Hamburg on the PETRA III storage ring. Both beamlines operate diffractometers constantly equipped with Mini-Kappa heads [1] as standard configurations. The regular horizontal-spindle MD2 at P13 provides sufficient mechanical accuracy for use with a mini-beam of 10 μ m diameter. At the microfocus beamline P14, a vertical-spindle MD3 diffractometer is installed that features an Omega sphere of confusion <200 nm [2]. On both beamlines, robotic sample mounting is assisted by Mini-Kappa devices.

Data collections using Mini-Kappa are fully integrated in the standard MxCuBE2 software, which was enhanced with the tools for implementing crystal re-orientations, centring corrections and queuing the multi-orientation data collections.

Along with the standard use for multi-orientation high multiplicity data collections, the series of less standard applications of Mini-Kappa are rising. Orienting a crystal mesh support to minimize the deviation of the mesh off the focal plane is an essential step of the rotation-method based scanning serial micro-crystallography [3] or automated multi-crystal methods as Mesh&Collect [4]. Similar procedures are crucial for precise optical centering of micrometer-sized crystals with high quality on-axis microscope. Furthermore, the beam size at P14 can be rapidly tailored to large crystals in two dimensions; the tailoring process is typically assisted by Kappa re-orientation which optimizes crystal perspective. Such tailored beams are highly demanded for crystals of large macromolecular complexes with very long unit cells of thousands of Å. Recently, Mini-Kappa in combination with flexible microfocusing and precise sample positioning at P14 has found a new application in experiments on structural dynamics. In such experiments the skimming arrangements are deployed, where one face of the aligned crystal is exposed to the exciting light and small crystal volume close to that face is probed by X-rays [5].

^{1.} S. Brockhauser, R.B.G. Ravelli and A.A. Mccarthy, The Use Of A Mini-K Goniometer Head In Macromolecular Crystallography Diffraction Experiments, (2013). *Acta Cryst.* D69, 1241-1251.

^{2.} F. Cipriani, F. Feisaz, C. Landret, A. Gobbo, D. Oss and G. Bourenkov (2012). 11th International Conference on Synchrotron Radiation Instrumentation, SRI.

^{3.} C. Gati, G. P. Bourenkov et al., Serial crystallography on *in vivo* grown microcrystals using synchrotron radiation, (2014) *IUCrJ* 1, 87-94

^{4.} U. Zander, G.P. Bourenkov et al (2015) MeshAndCollect: an automated multi-crystal data-collection workflow for synchrotron macromolecular crystallography beamlines, Acta Cryst. (2015). **D71**, 2328–2343

^{5.} I. Lundholm et al. Terahertz radiation induces non-thermal structural changes associated with Fröhlich condensation in a protein crystal, *Struct. Dyn.* 2, 054702 (2015)

Multi-axis Goniometry for MX at Diamond Light Source

R. Flaig

Diamond Light Source, Harwell Science and Innovation Campus, Didcot, OX11 0DE, United Kingdom <u>ralf.flaig@diamond.ac.uk</u>

ABSTRACT

Diamond Light Source [1] is the UK third generation synchrotron located south of Oxford and currently operates five beamlines for macromolecular crystallography (MX) and soon seven beamlines will serve the MX user community with state of the art facilities [2]. All MX beamlines provide tools for standard data collection but given the increasing complexity and associated challenges with bigger macromolecular complexes, membrane proteins and smaller crystals, different approaches are often required to get the best possible data out of these samples. Therefore, the different beamlines have started to specialize in order to address specific aspects of data collection to allow for successful structure solution. In this presentation I will focus on the implementation and use of multi-axis goniometers which are currently installed on three of the operational beamlines. There are many use cases where the application of multi-axis goniometry will be beneficial but there is some challenge involved to make users aware of the possibilities that the various tools provide and how to translate these into user-friendly procedures. An outlook on future plans will also be given.

REFERENCES

1. http://www.diamond.ac.uk

2. http://www.diamond.ac.uk/Mx.html

ABSTRACTS

Friday, November 13th, 2015

SESSIONS III & IV

MADaC - 2015

Friday, November 13th

SESSION III

Data processing for advanced data collection protocols

Chairperson: Pierre LEGRAND

- IT-07
 Inside the black box of data processing

 H. Powell
 Processing multi-axis, multi-wavelength and interleaved datasets with autoPROC

 C. Vonrhein
 C. Vonrhein
- IT-09 Diffraction experiments of arbitrary geometry *T. Grüne*

SESSION IV

Case studies

Chairperson: Serena SIRIGU

- IT-10The use of a mini-kappa goniometer head for diffraction experiments at the ESRF
A. McCarthyIT-11The use of multi-axis goniometers for phasing of glycoprotein crystals
- T. Krey
- IT-12 Experimental design in MX: A skill not to be ignored A. Thompson

Inside the Black Box of Data Processing

H. Powell

MRC Laboratory of Molecular Biology, Francis Crick Avenue, Cambridge, CB2 0QH, United Kingdom

ABSTRACT

Diffraction data collected on synchrotron beamlines is increasingly being processed *via* automated pipelines and new users have little idea of the steps involved in going from images to a file containing indexed, integrated and scaled reflections. I will take a look inside the "black box" and outline the methods involved in indexing, refinement of crystal and detector parameters, and of integration itself. While focussing on the methods implemented in Mosflm and its user interface iMosflm, the methods used in other programs will be discussed as well. The importance of the various statistics derived from scaling and merging of integrated intensities will be discussed.

- 1. A. G. W. Leslie and H. R. Powell, "Processing Diffraction Data with Mosfilm" in *Evolving Methods for Macromolecular Crystallography*, edited by R. J. Read and J. L. Sussman, 2007, **245**, pp. 41 51.
- 2. P. R. Evans and G. Murshudov, "How good are my data and what is the resolution", Acta Crystallogr. D69, 1204 1214 (2013).

Processing Multi-axis, Multi-wavelength and Interleaved Datasets with autoPROC

C. Vonrhein, C. Flensburg, P. Keller, W. Paciorek, A. Sharff & G. Bricogne

Global Phasing Ltd., Sheraton House, Castle Park, Cambridge CB3 0AX, UK

ABSTRACT

autoPROC¹ is a set of tools and programs to automate the whole range of steps involved in data processing: (1) analysis of collections of images and image headers, (2) indexing of diffraction images, (3) determination of accurate cell parameters, (4) integration of a series of images, (5) creation of files of intensities and amplitudes in various formats (MTZ, Scalepack), (6) automatic determination of most likely space group symmetry, (7) analysis of anomalous signal and (8) automatic determination of a sensible high-resolution limit. It contains special features for processing multi-sweep datasets, including (a) consistent indexing across sweeps, ensuring identical indexing for sweeps measured on the same crystal, by taking multi-axis goniostat settings into account, (b) internal scaling and merging of each sweep separately and (if applicable) (c) joint scaling of all sweeps simultaneously and merging of related sweeps after that scaling step.

autoPROC allows a detailed and general description of the underlying hardware, including more common multi-axis goniostats such as Kappa and Eulerian systems. It enables the detection of multiple lattices and ice-rings, also providing some initial treatment of those rather common artefacts at the stage of indexing, integration and scaling/merging (to avoid contamination of the final dataset). The computation of the positions and shapes of reflections expected to appear on each image is performed in simcal_predict⁶ and visualised using GPX2⁷, giving the user accurate and detailed feedback on the integration and parameter refinement process.

Detailed information allowing a user to understand each step, as well as providing help for further decision making, is presented as text and in graphical form. Recent developments have focused on the presentation of these results in HTML.

The present processing functionalities rely in part on third-party programs like XDS/XSCALE², POINTLESS³ and AIMLESS⁴ as well as on tools from the CCP4⁵ suite of programs.

REFERENCES

- M. D. Winn et al. (2011). Acta. Cryst. D67, 235-242.
- Partly supported by collaboration contract COL0044 between Global Phasing and the Diamond Light Source.

7. Initially developed by Wolfgang Brehm (while in the group of Kay Diederichs at University of Konstanz/DE) during an internship with Global Phasing during the Summer of 2014 with generous support by the MX group (particularly PX-III) of the Swiss Light Source.

Vonrhein, C. et al. (2011). Acta Cryst. D67, 293-302.
 Kabsch, W. (2010). Acta Cryst. D66, 125-132.
 P.R.Evans (2006). Acta Cryst. D62, 72-82.
 P.R. Evans & G.N. Murshudov (2013). Acta Cryst. D69, 1204–1214.

Diffraction Experiments of Arbitrary Geometry

T. Grüne

Swiss Light Source, Paul Scherrer Institute, Villigen, CH-5232, Switzerland

ABSTRACT

Single crystal diffraction is a powerful technique to determine the atomic structure of molecules. Multi–axis goniometers enable the collection of data with a high degree of multiplicity. In contrast to continued rotation about the same axis, "real" multiplicity reduces systematic errors. Inhouse data often reach a very high quality and the determination of the chirality of small organic compounds with only light atoms has become routine¹. Similarly, high–quality data from macromolecular structures improve the success rate of advanced phasing techniques like Sulphur SAD.

The program *XDS* is well–known for the integration and scaling of single crystal diffraction data². It is very fast and can be used non–interactively. These are two of the reasons why *XDS* is popular at synchrotron beamlines and used in various pipelines like *autoPRO*³ and *xia2*⁴. *XDS* can process virtually all types of crystallographic diffraction data with only very few requirements: the data must stem from a single crystal, collected with monochromatic radiation with the rotation method, and the detector must be built up from planar modules. Some of the more complicated scenarios include the pseudo–cylindrical detector P12M at the long–wavelength beamline I23 at the Diamond synchrotron⁵ and a dynamically changing shadow from the diamond Anvil cell used for high–ressure crystallography.

This talk will describe the coordinate systems used within *XDS*. The respective parameters from the *XDS* input file will be highlighted and also how to determine their values from a given setup. The concepts have been implemented in the program *sfrmtools* that facilitates the use of *XDS* with data frames in the Siemens Frame Format used by Bruker AXS. I will illustrate the theoretical description with some challenging data sets collected with four circle goniometers at home sources, with the κ -goniometer the the BESSY Synchrotron⁶ and our latest results to use *XDS* for electron diffraction data collected with a modified electron microscope⁷.

REFERENCES

⁵ http://www.diamond.ac.uk/Beamlines/Mx/I23.html

¹ S. Parsons, H. D. Flack, and T. Wagner. "Use of intensity quotients and differences in absolute structure refine-ment". In: Acta Crystallogr. B69 (2013), pp. 249–259.

² W Kabsch. "XDS". in: Acta Crystallogr. D66 (2010), pp. 125–132; Wolfgang Kabsch. "Integration, scaling, space-group assignment and post-refinement". In: Acta Crystallogr. D66 (2010), pp. 133–144.

³ C. Vonrhein et al. "Data processing and analysis with the autoPROC toolbox". In: Acta Crystallogr D67(2011), pp. 293–302.

⁴ M. D. Winn et al. "Overview of the CCP4 suite and current developments". In: Acta Cryst. D67 (2011), pp. 235–242.

⁶ K. Dalle et al. ^{*}A weakly coupled biologically relevant Cull 2 (μ – η 1 : η 1 – O2) cis-peroxo adduct that binds side-on to additional metal ions". In: J. Am. Chem. Soc. 136 (2014), pp. 7428–7434.

⁷ E. van Genderen et al. "Ab initio structure determination of nanocrystals of organic pharmaceutical compoundsby electron diffraction at room temperature using a Timepix quantum area direct electron detector". In revision at Acta Crystallogr. A.

The use of a Mini-kappa Goniometer Head for Diffraction Experiments at the ESRF

A. McCarthy

European Molecular Biology Laboratory, 71 avenue des Martyrs, Grenoble, 38042, France. andrewmc@embl.fr

ABSTRACT

Most macromolecular crystallography (MX) synchrotron based diffraction experiments use single-axis diffractometers. This markedly contrasts with small molecule crystallography, where the majority of diffraction data are collected using multi-axis goniometers. A novel miniaturised κ -goniometer head, the MK3, was developed by the EMBL-ESRF in Grenoble to allow the reorientation of macromolecular crystals (1). It is available on the majority of the structural biology beamlines at the ESRF, as well as elsewhere. The MK3 is fully controllable via MxCuBEv2 and to facilitate its use for advanced data collection strategies a number of protocols using a customized Passerelle-EDM based workflow engine called the *Beamline Expert System* have been developed (2). Here, I will present the current implementation of the MK3 on the MX-beamlines at the ESRF and how it can be used for advanced data collections. I will also present some recent results, illustrating how the alignment of macromolecular crystals can improve the success rate of diffraction experiments compared to data obtained from randomly aligned crystals.

REFERENCES

[1] Brockhauser, S., Ravelli, R. B. G., McCarthy, A. A. (2013) Acta Cryst. D69 1241-1251.

[2] Brockhauser, S., Svensson, O., Bowler, M. W., Nanao, M., Gordon, E., Leal, R. M. F., Popov, A., Gerring, M., McCarthy, A. A. & Gotz, A. (2012). Acta Crystallogr. D Biol. Crystallogr. 68, 975-984.

The Use of Multi-axis Goniometers for Phasing of Glycoprotein Crystals

T. Krey

¹Institut Pasteur, Unité de Virologie Structurale, 25-28 Rue du Docteur Roux, 75015 Paris, France ²CNRS UMR 3569, 25-28 Rue du Docteur Roux, 75724 Paris Cedex 15, France Present address: Institute of Virology, Hannover Medical School, 30625 Hannover, Germany

ABSTRACT

Soluble ectodomains of viral and cellular glycoproteins involved in membrane fusion can be challenging targets for crystallographers. These proteins are multi-domain proteins that are stabilized by a complex pattern of disulfide bridges and often highly glycosylated. In most cases these proteins are produced in eukaryotic expression systems like mammalian or insect cells. If crystallization is successful, crystals often diffract only to moderate resolution and can be difficult to reproduce due to heterogeneity in glycosylation and batch-to-batch variations.

In many cases the phase problem cannot be solved by molecular replacement. Production of selenomethionine (SeMet)-labelled protein is generally possible in eukaryotic expression systems, but a trade-off between the required SeMet concentration in the medium and the protein yield and SeMet incorporation level is observed to various extents in different expression systems. Therefore in many cases the production of derivative crystals for experimental phasing requires classical heavy atom screening.

Four case studies, in which we determined the crystal structure of glycoproteins involved in membrane fusion by experimental phasing will be presented. A particular importance will be given to the question, how the use of multi-axis goniometers and - tightly related to this low-dose exposure data collection strategies can contribute to this procedure.

Experimental Design in MX a skill not to be ignored

A. Thompson and the PROXIMA 1 beamline team, past and present.

Synchrotron SOLEIL, Gif-sur-Yvette, France

ABSTRACT

In the "age of the dinosaurs", when I collected my first X-ray data set from a protein crystal, the crystal was mounted, in a sealed but humidified environment, inside a capillary stuck to a goniometer head by plasticine and kept close to room temperature by a cooled nitrogen gas stream. Data recorded on X-ray sensitive film took a long time to develop (and even more to scan and analyse!), the onset of radiation damage was rapid and hence translation of the sample to "fresh parts of the crystal" a routine strategy. Data collection strategies were designed to measure all reflections with minimum sample exposure, and if you had collected 16 degrees of oscillation data in 30 minutes you were "doing very well". Crystals were changed regularly and the orientation of the fresh crystal chosen, using eye, ruler and International Tables volume A, to complete data already collected. It was impossible to collect data without looking at images and planning ahead. The questions posed from this "prehistoric era" will seem spookily familiar to modern crystallographers, even though the context was different.

Modern software tools give rapid feedback (post analysis, such as the various integration programs, parallelized and rapid) and advice (pre analysis, based on a subset of images and prior knowledge of beamline parameters) on both quality and completeness of data, and highly advanced software tools for structure solution have inbuilt intelligence, helping us avoid pitfalls for the unwary. With the help of huge advances in technology (detectors, nanopositioning...), beamlines have made huge strides in controlling the quality and alignment of X-ray beams, the goniometers that support crystals and the detection and quality of data. Nonetheless, as Z. Dauter remarked in his seminal paper on Data Collection Strategies (*Acta Cryst*, 1999, **D55** : 1703 - 1717), data collection is the last, crucial, and often very difficult or impossible to repeat, step in the chain of structure solution. When you have spent months or years optimizing your crystals, it is worth investing some thought before collecting the data.

This talk will present some indications as to the questions to ask when planning an experiment, as well as some of the reasons why I believe that these questions are still important.